

## SPECIFICATIONS

<b>Model:</b>	Mete-R-Matic III; product number 85423
<b>Drive:</b>	Wheels are driven by the ground, all six tires mechanically drive the conveyor and brush, no engine, no hydraulic system.
<b>Hopper Capacity:</b>	23 cubic feet (0.64 cubic meter)
<b>Hopper size:</b>	72" x 36" (1.83M x 0.92M) at top, tapering to 60" x 20" (1.5M x 0.51M) at bottom, 17-1/2" (0.45M) deep
<b>Spreading width:</b>	60" (1.5M)
<b>Top Dressing Speed:</b>	Up to 8 mph (12.8 Km/h)
<b>Transport Speed:</b>	Up to 15 mph (24 Km/h) empty, 8 mph (12 Km/h) loaded
<b>Conveyor Belt:</b>	Patented 60" (1.52M) wide <b>chevron</b> surface composition belt with heavy duty polyester cord. Exclusive front self cleaning roller.
<b>Application:</b>	From very fine to 1/4"
<b>Metering Gate:</b>	Taintor Gate Design is easily adjusted and provides a uniform opening up to 2-1/4" (57 mm).
<b>Brush:</b>	9" (228 mm) diameter, polypropylene bristle
<b>Controls:</b>	Electric clutch actuator to engage conveyor and brush. Metering gate control for depth of application.
<b>Clutch:</b>	The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle.
<b>Wheels and Tires:</b>	Six, 16 x 6.50 x 8 rib tread turf tires
<b>Differential:</b>	Wheels independently clutched for differential action. No scuffing during tight turns.
<b>Hitch:</b>	Heavy-duty pin hitch or 5th wheel hitch optional
<b>Weight:</b>	851 lbs. (386 Kg.)
<b>Shipping Weight:</b>	1,100 lbs. (499 Kg.)
<b>Shipping Dimensions:</b>	80-1/2" x 51" x 39-1/2" 93.9 cubic feet 2M x 1.27M x 1M, 2.5 cubic meters
<b>Also Available:</b>	657106 Six Wheel Conversion Kit adds the two center wheels to older Mete-R-Matics. 658020 Electric Clutch Actuator Kit adds the switch control to older Mete-R-Matics.

*Specifications subject to change without notice*