

SPECIFICATIONS

Model:	Mete-R-Matic® XL; product number 85460
Drive:	Wheels are driven by the ground, two tires mechanically drive the conveyor and brush, no engine, no hydraulic system
Hopper Capacity:	60.75 cubic feet (1.72 cubic meters; 2.25 cubic yards)
Payload:	6,000 lbs (2,721 kg)
Hopper Size:	80" x 65.5" at top, tapering to 60" x 46" at bottom, 18.5" deep
Spreading Width:	60" (1.5m)
Top Dressing Speed:	Up to 8 mph (12.8 km/h) when loaded
Brush:	9" dia. (228 mm) polypropylene bristle
Metering Gate:	Taintor Gate Design is easily adjusted and provides a uniform opening up to 2-1/4" (57 mm).
Controls:	Electrically operated clutch for conveyor and brush drive. Metering gate adjusted by hand.
Wheels:	Two, 33 x 15.50 - 16.5 flotation tires
Hitch:	Adjustable height clevis 1" pin hitch
Electrical Requirements:	12 volt DC, negative ground, electrical power provided by tow vehicle
Empty Weight:	2,110 lbs. (957 kg) Tow Vehicle Minimum 30 HP tractor (refer to Operator's Manual for additional requirements)

Specifications subject to change without notice