

SPECIFICATIONS

Product Number:	Model 86172
Dimensions:	Width...28 Inches (0.71 Meter) Height...27 Inches (0.69 Meter) (Bottom of Conveyor Frame to Top of Handle) Length66-1/2" Inches (1.69 Meters) (Without Hoses)
Operating Reach:	55 Inches (1.4 Meter) (Measured From End of Cross Conveyor to Center of Cross Conveyor Hopper)
Operating Swivel Angles:	0° to 180° Degrees.
Material Handling Rate:	Up to 8.1 Cubic Feet (0.3 Cubic Yards/0.23 Cubic Meters) Per Minute
Operating Ground Speed:	Stationary Use Only
Transport Speed:	Up to 9.6 Km/h (6 MPH) When Attached to the 1530 or 1530TM (1530 Cross Conveyor Must Be Properly Stowed During Transport)
Operator Controls:	ON/OFF Operation Controlled by 1530 Hand Held ON/OFF Switch. Operating Speed Controlled By 1530 Spinner Speed Control, Operates In Conjunction With 1530 Conveyor Belt Speed Control and Metering Gate Handle. Locking Handles on Cross Conveyor For Swivel Indexing Control and Transport/Storage Position.
Hydraulic Drive:	Hydraulic Motor Driven Conveyor Belt. Hydraulic Power Provided by 1530 (or truck).
Conveyor Belt:	Patterned 7" Inches (178 mm) Wide PVC Composition.
Weight:	155 Pounds (70.3 Kg)
Maximum Operating Angle of 1530and Conveyor Attachment During Transport and Stationary Operation	15° Degrees

Specifications subject to change without notice